

CU Distribution Cables

CU DISTRN-USC XL 2X 16^ 250m

Nexans Ref.: DEVP15VT302CXHF

Country Ref.: 6988.25

Cu conductors, XLPE insulation, Black PVC sheath. Vector Specification.

DESCRIPTION

Application

- Industrial, commercial and domestic applications.
- Recommended for distribution systems.



STANDARDS

National Customer specification

CU Distribution Cables

CU DISTRN-USC XL 2X 16[^] 250m

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
Type of conductor	Circular, stranded
Insulation	XLPE
Outer sheath	PVC
Core identification	Red,Black
Sheath colour	Black
With Green/Yellow core	No
With smaller neutral conductor	No

Dimensional characteristics

Number of cores	2
Conductor cross-section	16 mm ²
Nominal overall diameter	19.1 mm
Approximate weight	0.37 kg/m
Neutral conductor section (when smaller)	- mm ²

Electrical characteristics

Conductor AC resistance at 50 Hz	- Ohm/km
Inductive reactance at 50Hz	- Ohm/km
Insulation resistance at 20°C	- MOhm.km
Max. DC resistance of the conductor at 20°C	1.15 Ohm/km
Rated Voltage U _o /U (U _m)	0.6/ 1 (1.2) kV

Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

Usage characteristics













Max. conductor temperature in service	90 °C
---------------------------------------	-------

CU Distribution Cables

CU DISTRN-USC XL 2X 16^ 250m

CURRENT CARRYING CAPACITIES SINGLE PHASE (IN AMPS) - COPPER DISTRIBUTION, TWO CORE

Copper conductor Circular stranded Insulation XLPE Max. Conductor Temperature 90C

Conductor cross-section [mm²]	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu
16	114	107	90	141	105	54
 Air spaced from surface, unenclosed	 Air touching, unenclosed		 Air enclosed			
 Buried direct	 Buried in single-way duct		 Cable surrounded by thermal insulation, unenclosed			

Note

© Copyright Standards New Zealand 2012.

Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at www.standards.co.nz.

The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m